

CLAIM AMENDMENTS

1 Claim 1. (Original) A bar-shaped lamp comprising:
2 an elongated shaft;
3 a lamp head affixed to one end of said shaft and provided
4 with a light source; and
5 a reversible elongated foot member receivable in said
6 shaft at an opposite end of said shaft and having at a first end of
7 said foot member an elongated spike adapted to be inserted into the
8 ground and at a second end of said foot member an impact tool
9 capable of rupturing a vehicle window.

1 Claim 2. (Original) The bar-shaped lamp defined in
2 claim 1 wherein said light source includes at least one light-
3 emitting diode.

1 Claim 3. (Original) The bar-shaped lamp defined in
2 claim 2 wherein said light source includes a plurality of light-
3 emitting diodes.

1 Claim 4. (Original) The bar-shaped lamp defined in
2 claim 3 wherein said spike and said tool are both conical.

1 Claim 5. (Original) The bar-shaped lamp defined in
2 claim 4 wherein said spike and said tool have respective apex
3 angles with the apex angle of said spike being less than the apex
4 angle of said tool.

1 Claim 6. (Original) The bar-shaped lamp defined in
2 claim 5 wherein said foot member has a portion between said spike
3 and said tool which is flush with said shaft and adapted to be
4 inserted into said shaft.

1 Claim 7. (Original) The bar-shaped lamp defined in
2 claim 6 wherein said portion has a friction fit in said shaft.

1 Claim 8. (Original) The bar-shaped lamp defined in
2 claim 6 wherein said portion is threaded into said shaft.

1 Claim 9. (Currently amended) The bar-shaped lamp
2 defined in claim 6, further comprising a connection ~~replaceable~~
3 replaceably securing said lamp head on said shaft.

1 Claim 10. (Original) The bar-shaped lamp defined in
2 claim 9 wherein said connection is a threaded connection.

1 Claim 11. (Original) The bar-shaped lamp defined in
2 claim 10 wherein said lamp head comprises a plate, a plurality of
3 light-emitting diodes mounted on said plate and a spiral contact
4 spring resiliently engageable with a battery in said shaft.

1 Claim 12. (Currently Amended) ~~The bar-shaped lamp~~
2 ~~defined in claim 11, further comprising~~ A bar-shaped lamp
3 comprising:
4 an elongated shaft;
5 a lamp head affixed to one end of said shaft and
6 comprising a plate, a plurality of light-emitting diodes mounted on
7 said plate and a spiral contact spring resiliently engageable with
8 a battery in said shaft; and
9 a reversible elongated foot member receivable in said
10 shaft at an opposite end of said shaft and having at a first end of
11 said foot member an elongated conical spike adapted to be inserted
12 into the ground and at a second end of said foot member a conical
13 impact tool capable of rupturing a vehicle window, said spike and
14 said tool having respective apex angles with the apex angle of said

15 spike being less than the apex angle of said tool, said foot member
16 having a portion between said spike and said tool which is flush
17 with said shaft and adapted to be inserted into said shaft;
18 a threaded connection replaceably securing said lamp head
19 on said shaft; and
20 a plate, a plurality of light-emitting diodes mounted on
21 said plate and a spiral contact spring resiliently engageable with
22 a battery in said shaft;
23 a cap adapted to receive said tool and threaded onto said
24 foot member.

1 Claim 13. (Original) The bar shaped lamp defined in
2 claim 12, further comprising an elongated light-transmitting body
3 affixed to said head and illuminatable thereby.

1 Claim 14. (Original) The bar-shaped lamp defined in
2 claim 13 wherein said body is a rod of a light-conducting plastic.

1 Claim 15. (Original) The bar-shaped lamp defined in
2 claim 14 wherein said rod is composed of polymethylmethacrylate and
3 is threadedly connected to said shaft.

1 Claim 16. (Original) The bar-shaped lamp defined in
2 claim 1 wherein said shaft comprises a battery holder and a
3 compartment dimensioned to receive said spike.

1 Claim 17. (Original) ~~The bar-shaped lamp defined in~~
2 ~~claim 16, further comprising~~

3 A bar-shaped lamp comprising:
4 an elongated shaft;
5 a lamp head affixed to one end of said shaft and provided
6 with a light source;

7 a reversible elongated foot member receivable in said
8 shaft at an opposite end of said shaft and having at a first end of
9 said foot member an elongated spike adapted to be inserted into the
10 ground and at a second end of said foot member an impact tool
11 capable of rupturing a vehicle window, said shaft comprising a
12 battery holder and a compartment dimensioned to receive said spike;
13 and

14 a cap adapted to receive said tool and threaded onto said
15 foot member.

1 Claim 18. (Original) The bar-shaped lamp defined in
2 claim 17, further comprising an elongated light-transmitting of an
3 acrylic resin body affixed to said head and illuminatable thereby.

1 Claim 19. (Original) The bar-shaped lamp defined in
2 claim 18 wherein said lamp head comprises a plate, a plurality of
3 light-emitting diodes mounted on said plate and a spiral contact
4 spring resiliently engageable with a battery in said shaft.

1 Claim 20. (Original) The bar-shaped lamp defined in
2 claim 19 wherein said foot member has a portion between said spike
3 and said tool which is flush with said shaft and adapted to be
4 inserted into said shaft.